B Braun Perfusor Space Infusion Pump

SOMA TECHNOLOGY, INC.™

New, Demo & Refurbished Medical Equipment

B. Braun's **Perfusor Space** Infusion Pump — with advanced delivery features that offer safety and accuracy — is ideal for operating rooms, adult care, pediatric and emergency settings where ease of use and precise medication administration are critical. At just 9" x 6" and only 3 pounds, the compact and lightweight design of the **Perfusor Space** Infusion Pump allows easy transport and flexibility in crowded care settings.

Features

- Easy-to-learn, intuitive and user friendly 1,500-entry drug library available
- Alarms are audible, clearly visible and differentiated using different tones
- Strong lightweight pole clamp holds up to three pumps mounted horizontally or vertically



Soma Technology, Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA
Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com

Revised 8/22/2017

B Braun Perfusor Space Infusion Pump

Specifications

Physical	**Width:** 9.8 In *(24.9 cm)* **Height:** 2.6 In *(6.8 cm)* **Depth:** 5.9 In *(15.2 cm)* **Weight:** 1.08 lbs *(1.4 kg)*
Battery	**Type of Battery Pack:** NiMH (Rechargeable) **Operating Time:** Approx. 8 Hours at 25ml/h **Recharge Time:** Approx. 6 Hours
Environmental	**Operating Conditions** Relative Humidity: 30% - 90% (Without Condensation) Temperature: 41°F - 104°F *(5°C - 40°C)* Atmospheric Pressure: 500 - 1060 mbar **Storage Conditions** Relative Humidity: 30% - 90% (Without Condensation) Temperature: -20°F - 131°F *(-20°C - 55°C)* Atmospheric Pressure: 500 - 1060 mbar
Volume Preselection	0.1 - 99.99 ml in increments of 0.01 ml 100.0 – 999.0 ml in increments 0.1 ml 1000 – 9999 ml in increments 1 ml
Time Preselection	00:01 – 99:59 h
Accuracy of Set Delivery Rate	± 2 % according to IEC/EN 60601-2-24
Occlusion Alarm Pressure	9 levels up to 1.2 bar
Alarm in the Case of Incorrect Dose	For incorrect dosages of 0.1 ml due to malfunctions of the device the pump will automatically shut off.
External Power Supply	**Rated Voltage:** 100 - 240 V AC~, 50/60 Hz **External Low Voltage:** 11 - 16 V DC via Connection Lead SP 12 V or via SpaceStation

SOMA TECHNOLOGY, INC.™
New, Demo & Refurbished Medical Equipment

Soma Technology, Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA
Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com

Revised 8/22/2017