
BAum

Hc #01
p.1

Status	Item Num	Catalog	Mfg	Ab	MSDS	Description	Description 2
	045932	0120	BAUM		01	SPHYG, V-LOK KOMPAK ADLT	
DGM	174083	0200	BAUM		01	SPHYG, BANDAGE W/O WHEELS ADLT	
	029018	0220	BAUM		01	SPHYG, V-LOK W/O WHEELS ADLT	
	150158	0250	BAUM		01	SPHYG, V-LOK 4WHEELS ADLT	
DGM	174082	0260	BAUM		01	SPHYG, BANDAGE 4WHEELS ADLT	
DGM	149683	0300	BAUM		01	SPHYG, BANDAGE DESK MODEL ADLT	
	029020	0320	BAUM		01	SPHYG, V-LOK DESK MDL ADLT	
DGM	029021	0420	BAUM		01	SPHYG, V-LOK CREAM PANEL ADLT	
	029022	0620	BAUM		01	SPHYG, V-LOK HI/LO ADLT	
DGM	192856	0630	BAUM		01	SPHYG, V-LOK ADLT	
	029023	0820	BAUM		01	SPHYG, V-LOK W/CLIP NEUTRAL WH	T ADLT
DGM	118549	0820	BAUM		01	SPHYG, V-LOK W/CLIP BLU ADLT	
	243695	0821	BAUM		01	SPHYG, #33 WALL MODEL W/CLIP	
	174079	0833	BAUM		01	SPHYG, W/EXTENDABLE TU W/O INF	L OR CLP
	111541	0850	BAUM		01	SPHYG, V-LOK W/BASKET ADLT	
	349518	0850NL	BAUM		01	SPYG, V-LOK W/BSKT NLTX ADULT	
DGM	103535	0851	BAUM		01	SPHYG, V-LOK W/BASKET CHLD	
	177156	0870	BAUM		01	SPHYG, V-LOK W/LARGE BASKET	
DGM	051213	2110	BAUM		01	MERCURY, TRIPLE-DISTILLD(KOMPA	K,RX,HI/LO
	051922	2210	BAUM		01	MERCURY, TRIPLE-DISTILLED (STA	NDBY)
	047672	2310	BAUM		01	MERCURY, TRIPLE-DISTILLED(DESK	/PANEL/U33

Hc #01
p. 2



Baumanometer®

FAQ

SECTION I: **Manufacturer's Name** **Address**	W.A. Baum Co., Inc. 620 Oak Street Copiague, NY 11726	Tel: 631-226-3940 Fax: 631-226-3969
Product **Formula CAS No.** **Chemical Name**	Replacement mercury for Baumanometer® sphygmomanometer 7439-97-6, UN, NA #2809 Metallic mercury, hydrargyrum, quicksilver, Hg	
SECTION II, **SECTION III** **Boiling Point** (° F & ° C) **Specific Gravity** (H_2O=1) **Freezing Point** (° F & ° C) **Molecular Weight** **Vapor Pressure** (mm Hg) **Solubility in Water** **Appearance and Odor**	**COMPOSITION AND PHYSICAL PROPERTIES** 674°F, 356.7°C 13.55 -38.0°F, -38.87°C 200.59 0.0012 0.002g/100g Silvery liquid - no odor	
SECTION IV **NFPA Ratings** (scale 0-4) **CERCLA Ratings** (scale 0-3)	**HEALTH HAZARD DATA** Health=3 Fire=0 Reactivity=0 Health=3 Fire=0 Reactivity=0 Presistence=3	
SECTION V **Effects of Acute and Chronic Overexposure**	**HEALTH HAZARD DATA** No danger until vapor level exceeds 0.05 mg/m^3 (TWA); also see Section XI regarding overexposure	
Emergency and First Aid Procedures	See Sections VII and IX Not Carcinogenic	
SECTION VI **Stability** **Incompatibility (Materials to Avoid)**	**REACTIVITY DATA** Stable Acetylene, acetylene gases, ammonia gases, boron This material amalgamates with Au, Cu, Ag, Sn, Al	
Hazardous Decomposition Products **Hazardous Polymerization** **Conditions to Avoid**	Mercury vapor when heated Will not occur Heat, high temperature	
SECTION VII **Steps to be Taken in Case Material is Released or Spilled**	**SPILL OR LEAK PROCEDURES** Increase ventilation in area of spill, collect spilled material for reclamation, wear disposable gloves, draw up with a syringe	
Waste Handling and Disposal Method	Store in closed containers. Don not incinerated mercury or dispose of it inappropriately or improperly; recycle it	
Reportable Spill Quantity (RQ)	One pound or greater, CERCLA Section 103, SARA Section 304 A Baumanometer® instrument contains approximately 1/4 pound of	

HC #01
p.13

	mercury; about 2 teaspoonfuls
SECTION VIII	**OCCUPATIONAL PROTECTIVE MEASURES (For Persons Using Baumanometer® Replacement Mercury**
Ventilation	Provide local exhaust or dilution to meet permissible exposure limits
Protective Gloves	Suggested, latex or vinyl
Eye Protection	Suggested
SECTION IX: Handling and Storage Precautions	**SPECIAL PRECAUTIONS** Avoid breathing vapor, use adequate ventilation, wash skin with soap and water after contact, no drinking, smoking or eating where mercury is handled. Remove jewelry before handling. Do not heat. Work on a nonporous surface with a lip, clean up all droplets, wear disposable gloves.
SECTION X:	**TRANSPORTATION**
Shipping Name	Replacement Mercury
Hazard Class	DOT ORM-B, Corrosive
SECTION XI:	**EFFECTS OF ACUTE AND CHRONIC OVEREXPOSURE** **NOTE:** "Overexposure" occurs when an individual is exposed to toxic levels over an **extended** period of time
Acute Overexposure	Metallic taste, salivation, swelling of gums, vomiting, and bloody diarrhea
Chronic Overexposure	May show same symptoms as for acute, although less pronounced. Prolonged exposure over long periods of time may lead to a disease of the nervous system characterized by market tremor, unsteady gait, and personality changes. Sources of this information: NY State Department of Health; and Massachusetts Department of Labor and Industries.)

The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, W.A. Baum Co., Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular purpose. Accordingly, W.A. Baum Co., Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information.

No representation or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information set forth herein or to the product to which the information refers.

W.A. Baum, Inc.

FAQ Index

W.A. Baum Co., Inc., 620 Oak Street, Copiague, NY 11726
Toll Free Number 1-888 281-6061 Tel: 631.226.3940 Fax: 631.226.3969
© 2000 W.A. Baum Co., Inc. All Rights Reserved
Contact Us: info@wabaum.com