SAFETY DATA SHEET

Creation Date 07-May-2015 **Revision Date** 26-Jan-2015 **Revision Number** 1

1. Identification

Product Name **Clarifier I, Fisher Pinnacle Portfolio**

Cat No. : **22-050-116, 22-050-118, 22-220-107**

Synonyms No information available

Recommended Use In vitro diagnostic.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company
Richard Allan Scientific
A Subsidiary of Thermo Fisher Scientific
4481 Campus Drive
Kalamazoo, MI 49008
Tel: (800) 522-7270

Emergency Telephone Number
Chemtrec US: (800) 424-9300
Chemtrec EU: 001 (202) 483-7616

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 1
Skin Corrosion/irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Central nervous system (CNS), Optic nerve, Respiratory system.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

Label Elements

Signal Word
Danger

Hazard Statements
Extremely flammable liquid and vapor
Causes severe skin burns and eye damage
May cause drowsiness or dizziness
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure
May cause respiratory irritation



Precautionary Statements
Prevention
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool
Response
Immediately call a POISON CENTER or doctor/physician
Inhalation
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Skin
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Ingestion
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
Fire
In case of fire: Use CO2, dry chemical, or foam for extinction
Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed
Disposal
Dispose of contents/container to an approved waste disposal plant
Hazards not otherwise classified (HNOC)

Other hazards
Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	4 - 5
Ethyl alcohol	64-17-5	70 - 76
Methyl alcohol	67-56-1	4 - 5
Acetic acid	64-19-7	5 - 9.9
Water	7732-18-5	5 - 10

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

	Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required.
Ingestion	Call a physician or Poison Control Center immediately. Do not induce vomiting.
Most important symptoms/effects	Breathing difficulties. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use water spray to cool unopened containers.
Unsuitable Extinguishing Media	No information available
Flash Point	20.6 °C / 69.1 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical
Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products
Carbon monoxide (CO) Carbon dioxide (CO_2) Thermal decomposition can lead to release of irritating gases and vapors
Protective Equipment and Precautions for Firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
3	4	0	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.
Environmental Precautions	Should not be released into the environment. See Section 12 for additional ecological information.
Methods for Containment and Clean Up	Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment. Use explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m³ TWA: 400 ppm TWA: 980 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m³ TWA: 1000 ppm TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m³ Skin TWA: 200 ppm TWA: 260 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³
Acetic acid	TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m³ TWA: 10 ppm TWA: 25 mg/m³	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm TWA: 985 mg/m³ STEL: 500 ppm STEL: 1230 mg/m³	TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³	TWA: 200 ppm STEL: 400 ppm
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m³	TWA: 1000 ppm TWA: 1900 mg/m³	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³	TWA: 200 ppm STEL: 250 ppm Skin
Acetic acid	TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³	TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³	TWA: 10 ppm STEL: 15 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
OSHA - Occupational Safety and Health Administration
NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Clear
Odor	aromatic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	20.6 °C / 69.1 °F
Evaporation Rate	No information available
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Relative Density	No information available
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks.
Incompatible Materials	Strong oxidizing agents, Acids, Acid anhydrides, Acid chlorides
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO_2), Thermal decomposition can lead to release of irritating gases and vapors
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information	No acute toxicity information is available for this product
Oral LD50	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
Dermal LD50	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
Vapor LC50	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Ethyl alcohol	7060 mg/kg (Rat)	Not listed	20000 ppm/10H (Rat)
Methyl alcohol	6200 mg/kg (Rat)	15800 mg/kg (Rabbit)	64000 ppm (Rat) 4 h 83.2 mg/L (Rat) 4 h
Acetic acid	3310 mg/kg (Rat)	1060 mg/kg (Rabbit)	11.4 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Severe eye irritant

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	X	Not listed
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Acetic acid	64-19-7	Not listed	Not listed	Not listed	Not listed	Not listed
Water	7732-18-5	Not listed	Not listed	Not listed	Not listed	Not listed

IARC: (International Agency for Research on Cancer)

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects Mutagenic effects have occurred in humans.

Reproductive Effects Adverse reproductive effects have occurred in humans.

Developmental Effects Substances known to cause developmental toxicity in humans.

Teratogenicity Teratogenic effects have occurred in humans.

STOT - single exposure Central nervous system (CNS) Optic nerve Respiratory system
STOT - repeated exposure Kidney Liver spleen Blood

Aspiration hazard No information available

Symptoms / effects,both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects Tumorigenic effects have been reported in experimental animals. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	1000 mg/L EC50 > 96 h 1000 mg/L EC50 > 72 h	1400000 µg/L LC50 96 h 11130 mg/L LC50 96 h 9640	= 35390 mg/L EC50 Photobacterium	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

		mg/L LC50 96 h	phosphoreum 5 min	
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Acetic acid	-	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	EC50 = 95 mg/L/24h

Persistence and Degradability No information available
Bioaccumulation/ Accumulation No information available.

Mobility .

Component	log Pow
Isopropyl alcohol	0.05
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Acetic acid	-0.2

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT
- **UN-No** UN1170
- **Proper Shipping Name** ALCOHOLS, N.O.S. ETHANOL SOLUTION
- **Proper technical name** (Ethanol, Methanol)
- **Hazard Class** 3
- **Packing Group** II

TDG
- **UN-No** UN1170
- **Proper Shipping Name** ALCOHOLS, N.O.S. ETHANOL SOLUTION
- **Hazard Class** 3
- **Packing Group** II

IATA
- **UN-No** UN1170
- **Proper Shipping Name** ALCOHOLS, N.O.S. ETHANOL SOLUTION
- **Hazard Class** 3
- **Packing Group** II

IMDG/IMO
- **UN-No** UN1170
- **Proper Shipping Name** ALCOHOLS, N.O.S. ETHANOL SOLUTION
- **Hazard Class** 3
- **Packing Group** II

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Isopropyl alcohol	X	X	-	200-661-7	-		X	X	X	X	X
Ethyl alcohol	X	X	-	200-578-6	-		X	X	X	X	X
Methyl alcohol	X	X	-	200-659-6	-		X	X	X	X	X
Acetic acid	X	X	-	200-580-7	-		X	X	X	X	X
Water	X	X	-	231-791-2	-		X	-	X	X	X

Legend:
X - Listed
E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
P - Indicates a commenced PMN substance
R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
S - Indicates a substance that is identified in a proposed or final Significant New Use Rule
T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.
XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	4 - 5	1.0
Methyl alcohol	67-56-1	4 - 5	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Acetic acid	X	5000 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

Acetic acid	5000 lb	-

California Proposition 65 This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Developmental	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X
Ethyl alcohol	X	X	X	X	X
Methyl alcohol	X	X	X	X	X
Acetic acid	X	X	X	-	X
Water	-	-	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security
This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Canada
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class
B2 Flammable liquid
D1B Toxic materials
D2A Very toxic materials
E Corrosive material



16. Other information

Prepared By
Regulatory Affairs
Richard Allan Scientific
A Subsidiary of Thermo Fisher Scientific
Tel: (800) 522-7270

Creation Date 07-May-2015
Revision Date 26-Jan-2015
Print Date 26-Jan-2015
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS